



POS's VRX quick exhaust valves allow the possibility (if mounted on a pneumatic cylinder) to discharge rapidly the pressure contained inside it. Thanks to the material used for their realization (stainless steel AISI 316L), they allow the usage in particularly harsh or very delicate environments such as food and beverage and pharmaceutical.

POS VRX rychlo odvzdušňovací ventily umožňují možnost (pokud jsou namontovány na pneumatickém válci) rychle vypustit tlak uvnitř. Díky materiálu použitému k jejich realizaci (nerezová ocel AISI 316L) umožňují použití ve zvláště drsném nebo velmi citlivém prostředí, jako jsou potravinářství, nápojová technika a farmaceutický průmysl.



Le valvole a scarico rapido VRX di POS, consentono, se montate su di un cilindro pneumatico, di scaricare rapidamente la pressione in esso contenuta. Grazie al tipo di materiale con cui sono costruite, acciaio inox AISI 316L, permettono l'impiego in ambienti particolarmente gravosi o estremamente delicati come quello alimentare e farmaceutico.

## TECHNICAL DATA / TECHNICKÁ DATA / DATI TECNICI

Fluid / <b>Tekutina</b> / Fluido	Lubricated or non lubricated air / <b>Mazaný nebo nemazaný vzduch</b> / Aria con o senza lubrificazione
Pressure range / <b>Pracovní tlak</b> / Pressione di esercizio	2 - 10 bar
Temperature range / <b>Provozní teplota</b> / Temperatura di esercizio	-20°C / +180°C

## COMPONENTS / KOMPONENTY / COMPONENTI

Body / <b>Tělo</b> / Corpo	Stainless steel AISI 316L / <b>Nerezová ocel AISI 316L</b> / Acciaio inox AISI 316L
Seals / <b>Těsnění</b> / Guarnizioni	1/8 - 1/4 : FKM 3/8 - 1/2 - 3/4 - 1" : polyurethane / <b>polyurethan</b> / poliuretano



CODE	A	B	C	D	H	L	L1	CH
VRX0062	1/8	1/8	21	16,5	10	37,5	37	22
VRX0063	1/4	1/4	21	16,5	11	37,5	37	22
VRX0064	3/8	3/8	25,5	19	12	44,5	42	26
VRX0065	1/2	1/2	23	31	15	54	52	32
VRX0066	3/4	3/4	35	44	19	79	72	46
VRX0067	1"	1"	35	44	22	79	75	46